


* 45mm Dampen



Inner beam	Chassis	H-14572	Suspension	BPW SLU	Drawing bogie	P-8853, P-8852, P-8840 V/m P-8844
Extensions	Inner beam	K-15429	Axles	BPW HWZM, HWZMLL, 4xHWZFL	Side row	(7) UNP 160 closed, (8) UNP 240 closed
500	1st Center beam		Raise/lower	+140/-78 beiset	State pockets	96x66x6 2x11 pcs.
1000	2nd Center beam		Tyres	Michelin 245/70 R17.5 XTE2	Deck	28mm Hardw. 8/10mm Checker plate
1500	Outer beam	K-15430	Flth wheel load	18000 (techn. 28000)	Weidings	K-13320
2000	Special beam		Bogie load	34000 (techn. 72000)	Drain holes	#13
2500	Neck	H-12655/1	Landing gear	Joist Modul B	Type vehicle	6ABS-85
3000			Client	WESTDAK Exceptioneel Transport	Chassis number	XL965CSBA5L007105
3500						

COPYRIGHT BROSHUIS B.V. BROSHUIS HOLLAND		Specification modification Drawn EdB/F.V. Dimensions in mm Date 22-10-04 Scale 1:20 Order.no. Format A1 Preceded Tolerances ISO 2768-cl		Projection
BROSHUIS B.V. SPECIAL TRAILERS INDUSTRIEWEG 22 8263 AD KAMPEN POSTBUS 468 8260 AL KAMPEN TELEFOON +31(0)38 3372800 TELEFAX +31(0)38 3372888 E-MAIL sales@broshuis.com		Drawing no. 05105 Checked		

6-AXLE SINGLE EXTENDIBLE SEMI LOW LOADER